

# SMA, SMF and SBS Momentary Switches

	Diameter	Face	Function	Voltage	Connection	Material	Color
<b>S</b>							<b>N</b> Natural (only option for Steel) <b>B</b> Black <b>R</b> Red <b>G</b> Green <b>Y</b> Gold <b>L</b> Blue <b>Anodize Color</b>
							<b>1</b> Aluminum Type 6061 T651 <b>2</b> Stainless Steel Type 303/304 <b>Housing material</b>
							<b>P</b> Pins <b>W</b> Wires 22 AWG 30cm standard <b>C</b> Cable 60cm standard <b>Connection</b>
							<b>A</b> 0-24V 0.2A <b>B</b> 0-24V 1.0A <b>E</b> 0-24V 0.125A for N.Closed types <b>Voltage and Current</b>
							<b>A</b> N.O. <b>B</b> N.Closed (0.125A only) <b>C</b> 6 sec prolonged contact (N.O.) <b>Switch Function</b>
							<b>1</b> Flat face <b>2</b> Recessed face <b>4</b> Recessed face - square head <b>5</b> Flat face-chamfered edge 18mm <i>SMFstyle only</i> <b>6</b> Flat face-low profile <b>Face style</b>
							<b>MA</b> 22mm dia. mounting hole <b>MF</b> 16 or 18mm(SMF5) dia. mounting hole <b>BS</b> 19.5mm dia. mounting hole <b>Mounting Diameter</b>